

## Cool Light Fiber Optic Retractor System



*Various sized blades and light panels used  
with one retractor handle provide economy and  
diversity for a wide range of procedures*



# LumiView™ Cool Light Fiber Optic Retractor System

The LumiView™ Cool Light Fiber Optic Retractor System converts traditionally hot Xenon and Halogen light into cool, directional, uniform illumination. The LumiView™ retractor incorporates a unique quick-change blade design allowing for multiple blades to be used with one light guide handle. The single-use light panels deliver uniform, cool lighting even into the most difficult areas.



## LumiView™ Retractor Handle with Light Guide

B 61105

## "Mini" LumiView™ Blades

- B 61110 1/2" (12.5 mm) x 4" (10 cm)
- B 61111 3/4" (20 mm) x 4" (10 cm)
- B 61112 1" (24 mm) x 4" (10 cm)

## "Mini" LumiView™ Blades with Suction

- B 61111S 3/4" (20 mm) x 4" (10 cm) with Suction
- B 61112S 1" (24 mm) x 4" (10 cm) with Suction

## "Midi" LumiView™ Retractor Blades

- B 61115 1/2" (12.5 mm) x 5-3/8" (13.5 cm)
- B 61116 3/4" (20 mm) x 5-3/8" (13.5 cm)
- B 61120 1" (24 mm) x 5-3/8" (13.5 cm)
- B 61121 1-1/4" (30 mm) x 5-3/8" (13.5 cm)
- B 61125 3/4" (20 mm) x 7" (17.5 cm)
- B 61126 1-1/4" (30 mm) x 7" (17.5 cm)

## "Midi" LumiView™ Blades with Suction

- B 61116S 3/4" (20 mm) x 5-3/8" (13.5 cm) with Suction
- B 61120S 1" (24 mm) x 5-3/8" (13.5 cm) with Suction
- B 61121S 1-1/4" (30 mm) x 5-3/8" (13.5 cm) with Suction
- B 61125S 3/4" (20 mm) x 7" (17.5 cm) with Suction
- B 61126S 1-1/4" (30 mm) x 7" (17.5 cm) with Suction

## Light Panels

- B 61100 "Mini" Light Panel, 5/Box, Sterile
- B 61101 "Midi" Light Panel, 5/Box, Sterile



## Onyx-Lite; 50-Watt Solid State LED Light Source

A compact, efficient, durable "daylight" light. Color temperature of 6500° K nominal. Electronic (PWM)

intensity control from 0-100%. Typical LED life of greater than 50,000 hours.

B 78726 50-Watt Light Source with 4-Port Turret



## XS-300; 300-Watt Xenon Light Source

Provides superior illumination for unparalleled visualization of the surgical field. A field replaceable xenon bulb reduces unwanted

downtime and maintenance delays.

B 78730 300-Watt Xenon Light Source with 4-Port Turret

B 78731 Lamp Replacement, XS-300

B 78720 Mobile Stand for XS-300, Tip Resistant

B 78461 Surgical Headlight with 110 mm Spot

## Fiber Optic Cables

Cables are steam autoclavable and feature clear, silicon housing for easy viewing of damaged fiber optic strands.

B 79722 Storz/Storz, 5 mm x 9'

B 79725 Storz/Storz, 5 mm x 7.5'

B 79727 ACMI/ACMI, 5 mm x 7.5'

B 79765 ACMI/ACMI, 5 mm x 9'



To order or for additional information, contact Black & Black customer service at 877.252.2517 or 770.414.4880 or visit our on-line web store at [www.blackandblacksurgical.com](http://www.blackandblacksurgical.com).



5238 Royal Woods Parkway  
Tucker, GA 30084  
877.252.2517  
770.414.4880  
770.414.4879 Fax  
[www.blackandblacksurgical.com](http://www.blackandblacksurgical.com)